

Redi-Lock® 300 - Non-Conductive 300 PSI Push-On Hose

- **NON-CONDUCTIVE - TESTED TO ONE (1) MEGOHM PER INCH RESISTANCE MINIMUM**
- **MSHA APPROVED FLAME RESISTANT COVER**
- **EASY TO COUPLE**
- **LONG LENGTHS ON REELS**

APPLICATIONS:

- Low Pressure Pneumatic Systems
- Air Tools
- Water, Oil and Mild Chemical Solutions
- Robotic Welders

★Not recommended for unleaded gasoline

Special colors available in Blue, Gray and Red. Call for availability and or minimum run requirements.

Cover: *Black Nitrile/PVC*

Reinforcement: *Aramid Spiral Yarn*

Tube: *Nitrile*

Oil Resistance: *RMA - Class A*

Branding: *REDI-LOCK NON-CONDUCTIVE 300 PSI <size> MADE IN USA MSHA1C - 114/03*

Packaging: *MAXIMUM 2 PCS ON REEL*

1/4" - 5/8" ID hoses supplied on plastic reels, 3/4" ID hoses supplied on wooden reels



Service Temperature Range: -30°F (-34°C) to 180°F (+82°C)

Part Number	Color	ID (Inches)	OD (Inches)	Working Pressure (PSI)	Approx. Weight (lbs/100')	Reel Length (ft.)
REDI-LOC-04X700	Black	1/4"	1/2"	300	10	700
REDI-LOC-06X700	Black	3/8"	5/8"	300	13	700
REDI-LOC-08X700	Black	1/2"	3/4"	300	16	700
REDI-LOC-10X700	Black	5/8"	29/32"	300	23	700
REDI-LOC-12X700	Black	3/4"	1 1/32"	300	26	700