



<b>UFD</b>	
<b>Temperature Range:</b> -65F to 200F	
<b>Construction:</b> Thermoplastic polyurethane reinforced with a wire helix	
<b>Standard Colors:</b> Clear or black	
<b>Standard Lengths:</b> 25', 50'	
<b>Size Range:</b> 2" to 18"	
<b>Description:</b>	<ul style="list-style-type: none"> <li>● Superior abrasion resistance</li> <li>● Excellent flex fatigue resistance</li> <li>● Allows users to locate blockages</li> <li>● Handles higher pressure and vacuums than standard ducting</li> <li>● Materials used in UFD-Clear are FDA acceptable</li> <li>● Available with cuffed end finishes</li> <li>● Available in metric diameters, please consult us on minimums</li> </ul>
<b>Applications:</b>	<ul style="list-style-type: none"> <li>● Cotton Picking</li> <li>● Farming Equipment</li> <li>● FDA Acceptable Hoses</li> <li>● Food Grade</li> <li>● Furniture Manufacturing</li> <li>● LAV Disposal</li> <li>● Lawn Vacuum</li> <li>● Leaf/Lawn Collection</li> <li>● Material Handling</li> <li>● Oil Mist</li> <li>● Paper Mills</li> <li>● Parking Lot Sweepers</li> <li>● Peat Moss Vacuum</li> <li>● Powder &amp; Bulk</li> <li>● Sheet Metal</li> <li>● Street Sweeping</li> <li>● Textile Mills</li> </ul>