





Hose Ferrules



Hose ferrules for connecting hose and barbed hose fittings. Crimper required to install. Typically used with air and water hose. Available in Brass, Aluminum and Stainless Steel. Most applications require a ferrule ID no more that .025" larger than hose OD with fitting in place and a ferrule length of at least the length of the barb end of the barbed hose fitting.

Shown here are readily available sizes. Hundreds more are tooled and available.



Brass						
ID	Length (L)	Hole Size (H)		ID	Length (L)	Hole Size (H)
0.275"	0.500"	0.217"		0.675"	0.516"	0.500"
0.380"	0.718"	0.266"		0.687"	1.000"	0.500"
0.450"	0.500"	0.266"		0.718"	1.000"	0.625"
0.500"	0.500"	0.328"		0.750"	0.531"	0.500"
0.500"	1.000"	0.344"		0.750"	1.000"	0.625"
0.525"	1.000"	0.375"		0.781"	1.000"	0.625"
0.550"	0.550"	0.406"		0.812"	1.000"	0.625"
0.593"	1.000"	0.438"		0.875"	0.844"	0.688"
0.625"	0.550"	0.453"		0.975"	0.844"	0.688"
0.625"	1.000"	0.453"		1.150"	0.844"	0.875"
0.656"	1.000"	0.438"		1.375"	0.875"	1.125"

Aluminum						
ID	Length (L)	Hole Size (H)		ID	Length (L)	Hole Size (H)
0.375"	0.718"	0.266"		0.625"	0.550"	0.453"
0.450"	0.500"	0.265"		0.625"	0.968"	0.453"
0.500"	0.500"	0.328"		0.675"	0.500"	0.500"
0.550"	0.550"	0.406"		0.750"	0.550"	0.500"

304 Stainless Steel						
ID	Length (L)	Hole Size (H)		ID	Length (L)	Hole Size (H)
0.560"	1.000"	0.437"		0.690"	1.000"	0.500"
0.625"	1.000"	0.437"		0.750"	1.000"	0.625"
0.656"	1.000"	0.437"		1.175"	0.844"	0.875"