

60 DUROMETER SKIRTBOARD RUBBER

General Properties of 60 Durometer Skirtboard Rubber

- Excellent abrasion-resistance.
- Excellent weather-resistance

SPECIFICATIONS:

Blended SBR/NR slit sheet, Plate Finish:

Style SK60: 60 Duro hardness (Shore Durometer A)

Polymer: Styrene-Butadiene and
Isoprene Rubber, Natural

Color: Black

Common Name: Skirtboard Rubber

ISO/ASTM Designation: SBR/NR

PACKAGING: 50 Ft. Rolls

Style	ASTM Specification (SI units)	Temp. Range	Durometer	Tensile Strength (PSI)	Elongation (%)	Finish
SK60	D 2000 M1AA 608	-22°F to +158°F	55 – 65	1100	400%	Plate

ORDERING INFORMATION:

Item Number	Gauge x Width	Avg. Length (Linear Ft./Roll)	Approx. Wt./Roll
SK60-08x3x50	1/4" x 3"	50 ft.	23 lbs.
SK60-08x4x50	1/4" x 4"	50 ft.	30 lbs.
SK60-08x5x50	1/4" x 5"	50 ft.	38 lbs.
SK60-08x6x50	1/4" x 6"	50 ft.	45 lbs.
SK60-08x8x50	1/4" x 8"	50 ft.	61 lbs.
SK60-08x10x50	1/4" x 10"	50 ft.	76 lbs.
SK60-08x12x50	1/4" x 12"	50 ft.	91 lbs.
SK60-12x3x50	3/8" x 3"	50 ft.	34 lbs.
SK60-12x4x50	3/8" x 4"	50 ft.	45 lbs.
SK60-12x5x50	3/8" x 5"	50 ft.	57 lbs.
SK60-12x6x50	3/8" x 6"	50 ft.	68 lbs.
SK60-12x8x50	3/8" x 8"	50 ft.	91 lbs.
SK60-12x10x50	3/8" x 10"	50 ft.	114 lbs.
SK60-12x12x50	3/8" x 12"	50 ft.	136 lbs.
SK60-16x3x50	1/2" x 3"	50 ft.	45 lbs.
SK60-16x4x50	1/2" x 4"	50 ft.	61 lbs.
SK60-16x5x50	1/2" x 5"	50 ft.	76 lbs.
SK60-16x6x50	1/2" x 6"	50 ft.	91 lbs.
SK60-16x8x50	1/2" x 8"	50 ft.	121 lbs.
SK60-16x10x50	1/2" x 10"	50 ft.	151 lbs.
SK60-16x12x50	1/2" x 12"	50 ft.	182 lbs.
SK60-24x3x50	3/4" x 3"	50 ft.	68 lbs.
SK60-24x6x50	3/4" x 6"	50 ft.	136 lbs.
SK60-24x8x50	3/4" x 8"	50 ft.	182 lbs.
SK60-24x9x50	3/4" x 9"	50 ft.	205 lbs.
SK60-24x10x50	3/4" x 10"	50 ft.	227 lbs.
SK60-24x12x50	3/4" x 12"	50 ft.	273 lbs.
SK60-32x3x50	1" x 3"	50 ft.	91 lbs.
SK60-32x6x50	1" x 6"	50 ft.	182 lbs.
SK60-32x8x50	1" x 8"	50 ft.	242 lbs.
SK60-32x10x50	1" x 10"	50 ft.	303 lbs.
SK60-32x12x50	1" x 12"	50 ft.	363 lbs.
SK60-48x10x50	1 1/2" x 10"	50 ft.	455 lbs.